

Speed Enforcement

Hardware Specifications:

Weight:	2.4 lbs (1.09 kg)
Size:	6.75 x 2.75 x 5.75 in. (17.14 x 6.98 x 14.60 cm)
Construction:	All-aluminum extruded housing
Power Supply:	(2) AA batteries Up to 20 hours of use
Acquisition Time:	Speed Mode: 0.3 sec. Survey Mode: 0.4 sec.
Speed Accuracy:	+/- 1 mph (+/- 2 kph)
Speed Range:	+/- 200 mph (+/- 320 kph)
Range Accuracy:	Speed Mode: +/- 6 in. (15 cm) Survey Mode: +/- 2 in. (5 cm); typical +/- 6 in. (15 cm); max
Target Range:	Minimum - Speed Mode: 50 ft. (15 m) Survey Mode: 0 ft. (0 m) Maximum - 3,280 ft. (1 km)
Range Resolution:	0.01 ft. (0.01 m)
Temperature Range:	-22 to 140 F (-30 to 60 C)
Data Output:	RS232 Serial
Eye Safety:	FDA Class 1 (CFR 21)
Environment:	IP 67 and NEMA 6

Basic Package Includes:

- UltraLyte Compact laser
- (2) AA batteries
- Certification card
- Operator's manual
- Red-dot sighting scope
- Hand strap / tripod mount
- Padded carrying case

Key Features:

- Simplified menus and options for ease of use
- One-button weather filter (shoot through rain & snow)
- Ideal for just speed enforcement applications
- The most economical alternative to the standard UltraLyte series



Simplified Menus

Red-dot Sighting Scope

Hand-strap



*Please note that the UltraLyte Compact does not display the speed measurements inside the red-dot sighting scope. All measurements are displayed on the rear LCD.



UltraLyte LCD on rear panel

